



- NOTES:**
1. SEE DRAWING 403C FOR FOOTING DIMENSIONS AND REINFORCEMENT TABLE.
 2. PIER LOCATION DETERMINED BY ENGINEER.
 3. UNDER UNSTABLE CONDITIONS, ENGINEER PLANS FOR PIER DESIGN MUST BE SUBMITTED TO & APPROVED BY THE PUBLIC WORKS DEPARTMENT.
 4. PLACE PIERS AT EVERY BELL.
 5. ENGINEER TO SUBMIT PIER DESIGN.
 6. STEEL REINFORCEMENT TO BE A.S.T.M DESIGNATION A -15 - 54T UNLESS OTHERWISE SPECIFIED, BENDS IN BARS TO CONFORM TO A.C.I. STANDARD.
 7. PRECAST PIERS ARE ALLOWED PER PERMISSION OF COUNTY ENGINEER.
 8. PROVIDE 1/8 - INCH MINIMUM NEOPRENE PAD BETWEEN PIPE AND CLAMPS.

ELEVATIONS
NTS

TOP VIEW OF PIER CONNECTION
NTS

FULTON COUNTY STANDARD DETAIL 403A
CONCRETE PIER AND FOOTING DETAIL
ON SOIL

DATE	REVISIONS	DATE	REVISIONS
M/Y	XXX	M/Y	XXX

DGS/DRN/CHKD: XXX
APPROVED: XXX
DATE: XX-X-XX



FULTON COUNTY PUBLIC WORKS
141 PRYOR ST. ATLANTA, GA. 30303
404-612-7400 FAX: 404-224-0498

DRAWING NO.
403A

95% SUBMITTAL